neo:x
BY PULSEEIGHT

4X4 VIDEO MATRIX KIT



- EXTEND 1080P UP TO 40M
- EXTEND 4K UP TO 40M
- 4 HDMI INPUTS
- 4 HDBASET3 OUTPUTS
- 4 HDMI® OUTPUTS
- 4 AUDIO OUT ZONES
- CLOUD MONITORING

TECHNICAL SPECIFICATIONS


SKU: P8-HDBT3-L-FFMG48-KIT
HDMI Inputs: 4
Audio Outputs: 4 Audio Breakout Zones
HDBaseT Outputs: 4 HDBaseT3
HDMI Outputs: 4 Mirror HDMI®
HDBaseT Recommended Cable: Cat6A or higher
Ethernet Passthrough: No
IR Control: Bi-Directional
HDMI-CEC Control: Bi-Directional
Web Interface: Yes
Monitoring: Cloud Remote Monitoring Portal
Automatic EDID Management: Yes
HDMI ARC (Audio Return Channel): No
Compression: Uncompressed 4k UHD
PoH: Yes
Encryption: HDCP 1.4, HDCP 2.2 and HDCP 2.3
Maximum Pixel Clock: 600Mhz
Maximum Bandwidth: 18Gbps
Maximum Video Resolution: 4K@60Hz 4:4:4
Colour Supported: 4K 4:4:4: 8bit, 4K 4:2:2: 10bit
Third Party Control: Yes - Drivers available
Third Party Drivers Available: Control 4, Crestron, Elan, RTI, Savant
Power Consumption: 70W
Power Input: DC Input: 48.0V~ / 2.3A / 110W
Power Rating: 100-240V 4.0/2.0A 50/60Hz
Material: Powder Coated Aluminium
Product Dimensions: 44 x 12 x 4.4 cm - 1U (Matrix)
Product Weight: 913g (Matrix)
Operating Temp Range: 0 to +35°C (32 to +95°F)
Storage Temp Range: -20°C to 60°C (-4°F to 140°F)
Humidity Range: 5 to 90% RH (no condensation)
Safety & Emissions: UKCA, CE, FCC, RoHS
Manufactured In: Great Britain by Pulse-Eight

KIT INCLUDES

neo:4x Chassis | 4 x neo:Lite3 POH Receivers
Rack Mounting Kit | Power Adapter
Quick Start Guide | Infrared Cable Pack

HDMI HDBT HDCP2.3

CONCEPT WIRING DIAGRAM: neo:4x



LEGEND

- Infrared
- HDBaseT
- Ethernet
- HDMI

COMPATIBLE CONTROL SYSTEMS

CRESTRON ELAN Control4 RTI SAVANT

Pulse-Eight Limited . 8-12 Alder Hills . Poole . Dorset . BH12 4AL . UK
sales@pulse-eight.com | +44 (0)1202 413610 | www.pulse-eight.com

PULSEEIGHT